




SWITCH GUARDS & SHIELDS

Pushbutton Shields for Series C100, D200W, H2200, J300, W100 and WC1500 Switches

| FEATURES | DESCRIPTION |
|----------|-------------|
|----------|-------------|

- | | |
|--|--|
| <ul style="list-style-type: none"> Protection against accidental actuation Rugged construction Anodized for corrosion protection Threaded or unthreaded Available in black, clear or red Various size ranges | <p>These anodized aluminum shields guard pushbuttons against accidental operation. Internally threaded and unthreaded, the shields are usually used on basic switches in place of mounting adapters, although Type W or other narrow adapters can be used with shields. Consult switch and adapter drawings for proper thread size when ordering shields. Order shields separately by part number.</p> |
|--|--|

SELECTION TABLE

| | Type | Active P/N | Obsolete P/N | Color | Dimension "A" | Dimension "B" | Dimension "C" | Dimension "D" | Dimension "E" | | |
|---|---------------------|--|----------------|----------------|----------------|----------------|---------------|----------------|---------------|-----------|---|
|  | Knurled Shields | 73-2474 | 120011 | Clear Anodized | .625" | .875" | .500" | 1/2-32 NS-2B | — | | |
| | | 73-2474-2 | 102012 | Black Anodized | .625" | .875" | .500" | 1/2-32 NS-2B | — | | |
| | | 73-2474-3 | 102012 | Red Anodized | .625" | .875" | .500" | 1/2-32 NS-2B | — | | |
| | | 73-2475 | 120016 | Clear Anodized | .406" | .875" | .281" | 1/2-32 NS-2B | — | | |
| | | 73-2475-2 | 120017 | Black Anodized | .406" | .875" | .281" | 1/2-32 NS-2B | — | | |
| | | 73-2475-3 | 120018 | Red Anodized | .406" | .875" | .281" | 1/2-32 NS-2B | — | | |
| | Knurled Shields | 73-2486 | 120081 | Clear Anodized | .406" | .875" | .281" | 5/8-24 NEF-2B | — | | |
| | | 73-2486-2 | 120082 | Black Anodized | .406" | .875" | .281" | 5/8-24 NEF-2B | — | | |
| | | 73-2486-3 | 120083 | Red Anodized | .406" | .875" | .281" | 5/8-24 NEF-2B | — | | |
| | | 73-2487 | 120091 | Clear Anodized | .406" | .875" | .281" | 15/32-32 NS-2B | — | | |
| | | 73-2487-2 | 120092 | Black Anodized | .406" | .875" | .281" | 15/32-32 NS-2B | — | | |
| | | 73-2487-3 | 120093 | Red Anodized | .406" | .875" | .281" | 15/32-32 NS-2B | — | | |
| | |  | Smooth Shields | 73-2478 | 120031 | Clear Anodized | .688" | .957" | .641" | 1/2" HOLE | — |
| | | | | 73-2478-2 | 120032 | Black Anodized | .688" | .957" | .641" | 1/2" HOLE | — |
| 73-2478-3 | 120033 | | | Red Anodized | .688" | .957" | .641" | 1/2" HOLE | — | | |
| Smooth Shields | 73-2479 | | 120036 | Clear Anodized | .844" | .957" | .719" | 5/8-24 NEF-28 | — | | |
| | 73-2479-2 | | 120037 | Black Anodized | .844" | .957" | .719" | 5/8-24 NEF-28 | — | | |
| | 73-2479-3 | | 120038 | Red Anodized | .844" | .957" | .719" | 5/8-24 NEF-28 | — | | |
|  | Rolled Edge Shields | 73-2476 | 120021 | Clear Anodized | .422" | 1.063" | .375" | 1/2" HOLE | 61/64 | | |
| | | 73-2476-2 | 120022 | Black Anodized | .422" | 1.063" | .375" | 1/2" HOLE | 61/64 | | |
| | | 73-2476-3 | 120023 | Red Anodized | .422" | 1.063" | .375" | 1/2" HOLE | 61/64 | | |
| | | 73-2477 | 120026 | Clear Anodized | .688" | 1.063" | .641" | 1/2" HOLE | 61/64 | | |
| | | 73-2477-2 | 120027 | Black Anodized | .688" | 1.063" | .641" | 1/2" HOLE | 61/64 | | |
| | | 73-2477-3 | 120028 | Red Anodized | .688" | 1.063" | .641" | 1/2" HOLE | 61/64 | | |
| | | 73-2480 | 120041 | Clear Anodized | .422" | 1.063" | .375" | 5/8" HOLE | 61/64 | | |
| | | 73-2480-2 | 120042 | Black Anodized | .422" | 1.063" | .375" | 5/8" HOLE | 61/64 | | |
| | | 73-2480-3 | 120043 | Red Anodized | .422" | 1.063" | .375" | 5/8" HOLE | 61/64 | | |
| | | 73-2481 | 120046 | Clear Anodized | .610" | 1.188" | .563" | 5/8" HOLE | 1 3/32 | | |
| | | 73-2481-3 | 120048 | Red Anodized | .610" | 1.188" | .563" | 5/8" HOLE | 1 3/32 | | |
| | | 73-2485 | 120071 | Clear Anodized | .688" | 1.063" | .641" | 5/8" HOLE | 61/64 | | |
| | | 73-2485-2 | 120072 | Black Anodized | .688" | 1.063" | .641" | 5/8" HOLE | 61/64 | | |
| | | 73-2485-3 | 120073 | Red Anodized | .688" | 1.063" | .641" | 5/8" HOLE | 61/64 | | |
| | | Rolled Edge Shields | 73-2488 | 120106 | Clear Anodized | .500" | 1.063" | .375" | 5/8-24 NEF-2B | 61/64 | |
| | 73-2488-2 | | 120107 | Black Anodized | .500" | 1.063" | .375" | 5/8-24 NEF-2B | 61/64 | | |
| | 73-2488-3 | | 120108 | Red Anodized | .500" | 1.063" | .375" | 5/8-24 NEF-2B | 61/64 | | |
| | 73-2489-2① | | 120127 | Clear Anodized | .719" | 1.063" | .594" | 5/8-24 NEF-2B | 61/64 | | |
| | 73-2489-3① | | 120128 | Black Anodized | .719" | 1.063" | .594" | 5/8-24 NEF-2B | 61/64 | | |
| | 73-2489-4① | | 120129 | Red Anodized | .719" | 1.063" | .594" | 5/8-24 NEF-2B | 61/64 | | |
| | 73-2490 | | 120146 | Clear Anodized | .547" | 1.063" | .500" | 5/8" HOLE | 61/64 | | |
| | 73-2490-2 | | 120147 | Red Anodized | .547" | 1.063" | .500" | 5/8" HOLE | 61/64 | | |
| | 73-2490-3 | | 120148 | Black Anodized | .547" | 1.063" | .500" | 5/8" HOLE | 61/64 | | |

① May also be used with following mounting adapter types: A, B, D, DA, E, HA, P, PA, U, W.